



Critical Environment Overhead Ionizer

MODEL 5810i

The Simco-Ion Critical Environment Overhead Ionizer Model 5810i is designed to provide industry-leading balanced ionization performance in cleanroom environments. The Model 5810i is certified for use in ISO Class 4 cleanrooms (Fed. Std. 209(e) Class 10). The ionizer can operate with external sensors to maintain precise balance (better than $\pm 1V$) by altering ion output and adapting to environment changes. With the reliability of steady-state DC, the established method for eliminating the effects of ESD and ESD-induced electromagnetic interference (EMI) in high-tech facilities, the Model 5810i delivers maximum ion output where and when you need it.

Complete compatibility with the operating conditions in today's cleanrooms is ensured with silicone-free air bearing fans. Each fan is engineered for cleanliness, and sealed off from the rest of the chassis to meet critical cleanroom requirements. Ionizers that don't match these quality standards risk contaminating manufacturing processes and possibly reducing product yields.

Features

- $\pm 3V$ or better balance ($\pm 1V$ with the optional external feedback system)
- Cleanliness rated at ISO 14644 Class 4 (Fed. Std. 209e Class 10)
- Options for sensor input, FMS connection, alarms, and management control
- Auto-Clean System option

Benefits

- Provides the best corona-based ESD protection for maximizing yields
- Designed for use in an environment with a controlled level of contamination
- Increased control with immediate notification of alarms and the prevention of unauthorized adjustment to power or fan speed
- Automated emitter point cleaning for reduced maintenance cost and time



Specifications

Input Voltage	100-240 VAC (±10%), 50/60 Hz
Output Voltage	100-240 VAC, 50-60 Hz unfused, 5A max
Discharge¹	±1000-100V @ <3 sec, taken 18" away (45.7 cm) from the blower at high fan speed
Balance	±3V or better balance (±1V with the optional external feedback system)
Ion Emission	Steady-state DC
Emitter Points	ISO 14644 Class 4 (Fed. Std. 209e Class 10) titanium, 8 per fan
Airflow	108 cfm per fan (typ)
Cleanroom Class	Meets ISO 14644-1 Class 4 (Fed. Std. 209E Class 10)
Operating Env	Temperature 50-90°F (10-32°C); humidity 30-70% RH, non-condensing
Ozone	0.02 ppm or less
LED Indicators	Green POWER on; red FAULT alarm with optional AUDIBLE ALARM
Audible Noise	High fan speed 61 dB (typ); low fan speed 52 dB (typ); measurements taken 12" (30.5 cm) below fan
Mounting	Eye-bolts and S-hooks provided; U-shape bracket available
Controls	Balance adjust trimpot (1 per fan), 3-position fan switch (high/low/off) or fixed speed, sensor gain trimpot (optional; 1 per fan), sensor type or no sensor slide switch
Daisy-chain	10 units max; pwr cord (18 AWG) between units not to exceed 12" (304 mm) in length
Options	External sensor inputs, FMS 4-20 mA RJ-11 output (available with sensor option only), audible alarm, cord lock, Auto-Clean System
Enclosure	Aluminum chassis with epoxy-polyester powder coat
Dimensions	3.8H x 6.1D x 32L in. (9.6H x 15.5D x 81.3L cm); 3.8H x 6.1D x 40L in. (9.6H x 15.5D x 101.6L cm); 3.8H x 6.1D x 44L in. (9.6H x 15.5D x 111.8L cm)
Weight	Aluminum 44" unit 10.3 lb (4.6 kg)
Warranty	Two year limited warranty
Certifications	    

1. Tested in accordance with ANSI/ESD STM3.1-2015.

Ordering Information

91-5810i-CzzH	Powder-coated white aluminum blower ±3V, high fixed fan speed (zz = 32", 40" or 44" length)
91-5810i-CzzX	Powder-coated white aluminum blower ±3V, low/high fan speed, (zz = 32", 40" or 44" length)
92-5810i-CzzX*	Powder-coated white aluminum blower ±3V, low/high fan speed (zz = 32", 40" or 44" length)
92-5810i-CzzH*	Powder-coated white aluminum blower ±3V, high fixed fan speed (zz = 32", 40" or 44" length)
*=F	Lowers balance to ±1V; adds FMS output to any of the above 92 level part numbers
*=E	Adds auto emitter clean system (requires 1 per fan) to any of the above 92 level part numbers
*=A	Adds audible alarm to any of the above 92 level part numbers
25-20660	IEC power cable cord, US plug, 8.2 ft (2.5m)
25-0670	IEC power cable cord, US plug, 10 ft (3m)
25-0680	IEC power cable cord, US plug, 15 ft (4.6m)
25-0700	IEC power cable cord, no plug, 10 ft (3m)
25-20710	IEC power cable cord, UK plug, 8.2 ft (2.5m)
25-20735	IEC power cable cord, German-Schuko plug, 8.2 ft (2.5m)
25-20750	IEC power cable cord (China Plug), 8.2 ft (2.5m)
25-0720	Daisy-chain power cord
32-6405	U-shaped mounting bracket (2 needed per blower)

Note: May add any combination of -F, -E or -A options to the 92 level part number.

Fan Speed Choices

The 5810i was designed specifically for use in cleanrooms up to and including ISO 14644 Class 4 (Fed. Std. 209(e) Class 10) in cleanliness. To minimize disruption of laminar airflow, the unit has a 3-position fan setting that optimizes static discharge performance with the smallest volume and velocity of airflow.

Factory Monitoring System

The blower includes an LED alarm light that indicates a range of possible conditions, including absence of ionization at the emitter points, or a stopped fan. An optional Audible Alarm is available. The optional Facility Monitoring System (FMS) feature provides an industry-standard 4-20 mA signal to your work cell controller for remotely monitoring error detection.

Auto-clean System

The optional, Auto-clean System is an automated feature that provides reduced operation costs due to lower maintenance. The Auto-clean System features a brush mechanism that sweeps the emitter points when the blower is turned off and on, allowing the Model 5810i to continually perform at optimum ion output and balance.



±1V Balance Performance

The Model 5810i ionizer's optional external feedback sensor operates with the Novx 7000 Process Monitor and with the Novx 3352 Passive or Novx 3362 Active Closed-loop Ionizer Controllers to detect and automatically correct the balance. With the antenna placed at the target area, feedback is sent to the Model 5810i blower's internal control system. This ensures that your target maintains a ±1V or better balance at all times.



Daisy-Chain Connections

The Model 5810i Blower may connect with other Model 5810i Blowers (daisy-chain) in series using the female AC outlet provided on one end of the Blower. Up to 10 Blowers may be connected together.



SIMCO IONTM
An ITW Company

DS-5810i_V4 - 4/17
© 2017 Simco-Ion
All rights reserved.

Simco-Ion

Technology Group
1601 Harbor Bay Pkwy, Ste 150
Alameda, CA 94502

Tel: +1 (800) 367-2452 (in USA)
Tel: +1 (510) 217-0600

ioninfo@simco-ion.com
www.simco-ion.com