



Digital Room Ionization System

MODEL 5515 CEILING EMITTER MODELS 5522/5582 CONTROLLERS IONMANAGER PRO SOFTWARE

The Model 5515 Ceiling Emitter and Controller Models 5522/5582 comprise our state-of-the-art digital room ionization system. The two controller models enable the user to start with the Model 5522 controller, capable of controlling a small system with 20 or fewer ceiling emitters, and grow into a large system with full software monitoring capabilities by simply moving to the Model 5582 Controller. Digital technology allows each ceiling emitter's parameters, including ion output, ion pulse timing, or digital address, to be either individually set at its location using the Model 5571 and Model 5572 Handheld Terminals or remotely set through IonManager Pro when integrated with the software. Precision fine-tuning of each ceiling emitter enables the ionization system to achieve maximum performance in any airflow condition and for each application.


IonManager Pro software provides a visual management tool to monitor and manage the system, including alarm conditions, room layouts, and individual emitter and controller status. Automated notifications for alarm conditions and maintenance alerts are user-controlled. Data logging provides a history of system changes, and security levels assure access by only authorized users.

Features

- Fully digital technology
- Single-crystal Silicon or Titanium emitter points
- Advanced Feedback Technology
- Small and large capacity controllers

Benefits

- Provides precision control of all ionization parameters with expansive data output capabilities
- Ensures ultra-clean performance with low maintenance; Single-crystal Silicon emitter points offer compatible material for leading-edge wafer processing applications
- Maintains balanced, high ion output over long periods for stable performance between emitter point cleanings
- Enables user to grow from a small system with FMS output only to a large system using IonManager Pro software as requirements change




Model 5515	
Input Voltage	24 VAC, 50/60 Hz, 1W (typ)
Output Voltage	0-20 kVDC for each polarity; positive and negative output levels adjusted separately
Ion Emission	Pulsed DC, Steady-state DC, or standby
Emitter	Single-crystal Silicon or Titanium replaceable emitter points
Emitter Rod	2.5, 5, 10, 15, 24, 36, 60, 66" (6.4, 12.7, 25.3, 38.1, 61.0, 91.4, 152.4, 167.6 cm), custom length is available
Cleanroom Class	Single-crystal Silicon ISO 14644-1 Class 1; Titanium ISO 14644-1 Class 3 standards
Connector	Telephone-type RJ-11 modular jack receptacle on each end of emitter
Control Signal	Ionization parameters are adjusted with the 5571 Handheld Terminal, 5572 IR Remote, or via IonManager Pro software
Timing	Precise timing (0-10 sec @ 0.1 sec resolution) is generated by a local microcontroller; LEDs on each emitter indicate the polarity of the ion emission
Regulation	Output and balance stability is achieved by independently regulating the ion emission current of each polarity at each emitter
Alarm	Alarm operates when emitter is no longer able to maintain preset ion output level; visual LED in the middle of the emitter; optional audible alarm at controller
Ozone	<0.005 ppm
Operating Env	59-95°F (15-35°C) nominal; 20-60% RH, non-condensing
Dimension	1.2"H x 1.4"W x 17.5"L (3.1 x 3.6 x 44.5 cm)
Weight	1.03 lb (0.465 kg)
Warranty	Two year limited warranty



Model 5522 & 5582 Digital Controllers	
Input Voltage	100/115/220-240 VAC ±10%, 50/60 Hz voltage selectable and fuse protected
Output Voltage	24 VAC
Capacity	Model 5582: 80 Model 5515 Ceiling Emitters Model 5522: 20 Model 5515 Ceiling Emitters
LED Indicator	Green POWER; red ALARM, AUDIBLE ALARM
Output Signal	RS-485 to Emitters (5522 & 5582); Ethernet or RS-485 to IonManager Pro (5582 only)
FMS Output	Relay or 4-20 mA output (available on both Model 5522 and 5582 controllers; no software capability on the Model 5522 controller)
Dimension	Model 5582: 6.2"H x 4.4"W x 13.2"L (15.8 x 11.1 x 33.5 cm) Model 5522: 3.0"H x 2.8"W x 12.4"L (7.5 x 7.0 x 31.6 cm)
Weight	Model 5582: 7 lb (3.18 kg); Model 5522: 3.2 lb (1.4 kg)
Certification	CE, UL US, RoHS2, UK CA

System Performance Security

The Model 5515 Ceiling Emitter, Model 5582 Controller and IonManager Pro software provide consistent ionization protection throughout your facility. The advance notification system communicates system alarms and warnings immediately so corrective action can be taken. The alarm notifications are user configurable and can be sent to multiple personnel via email, SMS, or pager.



Emitters are connected to the Model 5582 Controllers, which communicate with IonManager Pro to send email notifications to a facility monitoring system or agent.

Ordering Information

91-5515C-xxR	Digital Ceiling Emitter with titanium emitter points available in 2.5, 5, 10, 15, 24, 36, 60" rod lengths
91-5515U-xxR	Digital Ceiling Emitter with single-crystal silicon emitter points available in 2.5, 5, 10, 15, 24, 36, 60, 66" rod lengths
91-5522-01	Digital Controller, supports up to 20 emitters*
91-5582R	Digital Controller, supports up to 80 emitters*
91-5582-SW-Vx	IonManager Pro software (x represents current version number)
91-5572	Infrared Remote Controller for 5515 emitter
91-5571	Handheld Terminal

* IEC power cord require, contact Sales Service for detail.



An ITW Company

DS-5515_V9 - 1/23
© 2023 Simco-Ion
All rights reserved.

Simco-Ion, Technology Group

1141 Harbor Bay Parkway, Suite 201
Alameda, CA 94502

Tel: +1 (800) 367-2452 (in USA)
Tel: +1 (510) 217-0460

ioninfo@simco-ion.com
www.simco-ion/technology