



## MP AeroBar<sup>®</sup> Accessories MODEL 5630 / 5635(M) / 5645(A)(N)

The MP AeroBar is engineered to deliver industry-leading ionization performance for semiconductor backend advanced packaging and test applications and front-end ultra-clean environments. It ensures fast discharge times, low swing voltages, and precise ion balance. This advanced design allows mounting within 150 mm of the wafer, optimizing performance in space-constrained or high-sensitivity zones.

A range of accessories is available to optimize the MP AeroBar for specific application requirements.

## **Features**

- Mounting Clips and Brackets
- 5601 Power Distribution Box
- Various Emitter-Nozzles
- Available with Closed-loop Feedback features

## **Benefits**

- Designed specifically to fit in MP AeroBar chassis
- Bracket options offer mounting flexibility
- Can be used to mount the MP AeroBar vertically or horizontally
- Allows for connecting max 8 bars with alarms and power

SIMCO

An ITW Company

- Specifically designed with tool so to be easy removal for cleaning or replacement
- Rod Antenna Kit for the 5645A is available; or a Novx Antenna can be connected to enable enhanced performance monitoring and control through the Novx system



Signal and Power Junction Box for 1 MP Bar			
33-25625		24 VDC Power Converter Box with Signal and Power Junction Box Kit	
33-21491	signal in the second se	Signal and Power Junction Box for FMS connection	
92-5635-001	-	MP AeroBar Serial Adapter Kit (2-port RJ-45 Splitter/Combiner, RJ-45 to DB9 Adapter, USB to Serial Adapter included)	
5601 Power Distribution Box (8 bars max)			
33-5601-03		Power Distribution Box	
14-21241		Power Supply (Power Distribution Box only) (an appropriate power cord is required)	
Mounting Clips/Brackets (Models 5630 / 5635 / 5645(A)(N)			
28-6370		Flat mounting clip	
33-5353	e e	Flat clip with active/screw fastener	
32-22210	0 ° *	Adjustable horizontal mounting bracket	
32-22220		Vertical mounting bracket	
Mounting Brackets (Model 5635M)			
32-2212-01	4	Delrin® Plastic Bracket Clamp	
32-2214-01		Delrin® Plastic Bracket Swivel	
32-2215-01		Delrin® Plastic Clamp/Swivel Kit	
33-2215-01	Ser.	Delrin® Plastic Bracket Assembly	

Emitter Nozzles (Models 5630 / 5635(M) / 5645(A)(N)			
71-25660		QTC27 TurboJet Emitter Nozzle with Titanium Emitter Point, standard for 5630	
71-25380		QOC30 OpenJet Emitter Nozzle with Titanium Emitter Point	
33-5385-01		QOU30 OpenJet Emitter Nozzle with Single-crystal Silicon Emitter Point, standard for 5635/5635M	
33-5386-01: No-Air-Hole OpenJet Emitter Nozzle is available (optional for 5635M)			
33-5391-01		LPOU OpenJet Low Profile Nozzle with Single-crystal Silicon Emitter	
33-5390-01: No-Air-Hole Low Profile Nozzle is available			
32-5391-INST	Ø	LPOU Low Profile Nozzle Installation Tool	
Network Cables			
25-0540-6 25-0540-10 25-0540-15		CAT-5 RJ-45 Network Cable for connecting MP Bar to Junction Box or Distribution Box	
Rod Antenna Kit (Model 5645A)			
33-0545-zzz-01		SMA Rod Antenna Kit (zzz = 350, 450, 600, 850 mm lengths and bar length 850 mm or longer, use 850 mm Rod Antenna), RoHS	
Novx Passive Anter	nnas (Model 5645A)		
33-0521-xx	Passive Antenna, 1.75" x 1" tall with SMA-to-SMA Cable ( $xx = 5$ , 10, 20 ft lengths)		
33-0504	Passive Antenna, 1.75" x 4" tall with SMA-to-SMA Cable (5 ft)		
Novx Network Cable (Model 5645N)			
33-1620/30-xx	RJ-11 Cable for connecting 5645N to Novx Series 7000/3352/3362 (xx = 6, 10, 20 ft length)		
Software			



DS-5645-accessories\_V1 - 7/25 © 2025 Simco-Ion All rights reserved.

## Simco-lon, Technology Group

1141 Harbor Bay Parkway, Suite 201 Alameda, CA 94502 Tel: +1 (800) 367-2452 (in USA) Tel: +1 (510) 217-0460 ioninfo@simco-ion.com www.simco-ion.com